

**CA-Activator Spray****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product CA-Activator Spray
Code-Nr. 125002

**1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended intended purpose(s)**

Technical Aerosols
to accelerate the curing of cyanacrylat adhesives.

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories Hazard Statements Classification procedure

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.

H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07



GHS09

Signal word

Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

Naphtha (petroleum), hydrotreated light

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

3.2. Mixtures**Description**

Mixture of active ingredients with propellant

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	0,1 < 1	Acute Tox. 3, H331 / Acute Tox. 3, H311 / Acute Tox. 3, H301 / STOT RE 2, H373 / Aquatic Chronic 3, H412
106-97-8	203-448-7	butane	10 - 24,99	Flam. Gas 1, H220 / Press. Gas
74-98-6	200-827-9	propane	10 - 24,99	Flam. Gas 1, H220 / Press. Gas, H280
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	50 < 75	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336

REACH

CAS No	Name	REACH registration number
99-97-8	N,N-dimethyl-p-toluidine	01-2119956633-31
106-97-8	butane	01-2119474691-32
74-98-6	propane	01-2119486944-21
64742-49-0	Naphtha (petroleum), hydrotreated light	01-2119475514-35

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Medical treatment.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

Unconsciousness

Delirious state

Anaesthetic state

Headache

Confusion

Dizziness



4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into surface waters/groundwater.

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Allow to vaporise.

Keep at a distance of water, take up dry, wear breathing apparatus and personal protective clothing.

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

! Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

**CA-Activator Spray****General protective measures**

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

! Hygiene measures

At work do not eat, drink, smoke or take drugs.
Keep separated from food and feed.
Wash hands before breaks and after work.

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.
Do not pierce or burn even after use.
The product is combustible.
Vapours can form an explosive mixture with air.
Take precautionary measures against static discharges.
Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

! Further information on storage conditions

Protect from heat and direct solar radiation.
Keep container dry, tightly closed and store at cool and aired place.
Storage temperature may not exceed 50°C (=122°F).
Recommended storage temperature: room temperature.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	2038 mg/m3	DNEL long-term inhalative (systemic)	
		773 mg/kg	DNEL long-term dermal (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.
Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

! Hand protection

Gloves (solvent-resistant)

**CA-Activator Spray**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

colourless

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	-44,5 °C				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not applicable				
Flammable (solid)	not applicable				
Flammability (gas)	not determined				
Ignition temperature	200 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,8 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	8300 hPa	20 °C			
Relative density	0,638 g/cm3	20 °C			
Vapour density	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.04.2019 (GB) Version 8.9

CA-Activator Spray

	Value	Temperature	at	Method	Remark
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	99,8 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Risk of bursting.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5840 mg/kg	rat		Information concerns to main component.
LD50 acute dermal	> 2920 mg/kg	rabbit		Informations concern to main component.
LC50 acute inhalation	> 25 mg/l (4 h)	rat		Informations concern to main component.
Skin irritation	irritant			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

! Experiences made from practice

Vapours may cause dizziness, headaches and tiredness

At higher concentrations: narcotic effect, symptoms of being drunk or agitated

Frequent persistent contact with the skin may cause skin irritation.

Irritates mucous membranes.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The declarations of toxicology refer to main component.

**! SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LL/EL/IL50 11,4 mg/l (96 h)	Oncorhynchus mykiss		Information refers to the main component.
Daphnia	LL/EL/IL50 3 mg/l (48 h)	Daphnia magna		Information refers to the main component.
Algae	LL/EL/IL50 30 - 100 mg/l (72 h)	Pseudokirchneriella subcapitata		Information refers to the main component.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**! General regulation**

Toxic to aquatic life, fishes and plankton.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

! SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

07 01 04*

20 01 99

Name of waste

other organic solvents, washing liquids and mother liquors

other fractions not otherwise specified

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

! General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**CA-Activator Spray****SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS (Naphtha (petroleum), hydrotreated light)	AEROSOLS (Naphtha (petroleum), hydrotreated light)	Aerosols, flammable (Naphtha (petroleum), hydrotreated light)
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	Yes	Yes	Yes
14.6. Special precautions for user Caution: Gases			
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable			
Land and inland navigation transport ADR/RID Hazard label(s) 2.1 tunnel restriction code D Classification code 5F transport in "limited quantities" according to 3.4 ADR is possible			
Marine transport IMDG MARINE POLLUTANT			

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content	99,75 %
VOC value	636,4 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.
For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL Code 5-6

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.8

H220 Extremely flammable gas.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 02.04.2019 (GB) Version 8.9

CA-Activator Spray

H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.